



# ARK2500XE 2kVA

Life Goes On...



## DIESEL GENERATOR SETS

Type	Open
Phase	Single
Rated Frequency (Hz)	50
Rated Voltage (V)	230
Rated Power (kVA / kW)	1.8
Max Power (kVA / kW)	2,0
Power Factor	COS $\phi$ = 1
Rated Current (A)	7,8
Total Harmonic Content	$\leq 10\%$
Ambient Temperature	$\leq -10 / \leq 40^{\circ}\text{C}$
Insulation Class	F
DC Output (V)	12
DC Current (A)	2
Number of Poles	2
Excitation Type	AVR (Automatic Voltage Regulator), Brush
Dimensions L x W x H (mm)	640 x 460 x 520
Net Weight (kg)	63

## ENGINE

Model	ARK170F
Type	Air-Cooled, 4-Stroke, 1-Cylinder
Engine Power (hp)	3,4
Engine Speed (rpm)	3000
Bore x Stroke (mm)	70 x 55
Displacement (ml)	211
Compression Ratio	20:1
Fuel Type	Standard Diesel
Fuel Tank Capacity (L)	12,5
Fuel Consumption (l/h)	$\leq 0,67$
Continuous Running Time	12
Lubrication Quality	SAE10W30 (CD class and above)
Lubrication Type	Combined force - feed and splash lubrication
Starter	Electric Start

## FEATURES / STANDART / OPTIONAL EQUIPMENTS

Fuel Level Gauge	√
Engine Start Key	√
Digital Multimeter	√
AC Circuit Breaker	√
Socket (2x16A)	√
Lamp	√
Wheels & Handler	√
Battery - 22Ah (For electrical start)	√
Counter	√
12V DC Outlet (100W)	√
DC Circuit Breaker	√
Remote Start	O
CE Certificate	√
20 Feet	168 Units
40 Feet HQ	340 Units