



ARK11000Q-3 10,3 kVA

Life Goes On...



DIESEL GENERATOR SETS

Type	Canopy
Phase	3
Rated Frequency (Hz)	50
Rated Voltage (V)	230 / 400
Rated Power (kVA)	9,4
Max Power (kVA)	10,3
Power Factor	COS φ = 0,8
Rated Current (A)	13,,58
Total Harmonic Content	≤10%
Ambient Temperature	≤40°C
Insulation Class	F
DC Output (V)	12
DC Current (A)	8,3
Number of Poles	2
Excitation Type	AVR (Automatic Voltage Regulator), Brush
Dimensions L x W x H (mm)	1120 x 692 x 764
Net Weight (kg)	210

ENGINE

Model	ARK1100F
Type	Air-Cooled, 4-Stroke, 1-Cylinder
Engine Power (hp)	12,7
Engine Speed (rpm)	3000
Bore x Stroke (mm)	100 x 85
Displacement (ml)	0,667
Compression Ratio	20:1
Fuel Type	Standard Diesel
Fuel Tank Capacity (L)	26
Fuel Consumption (l/h)	≤2,75
Continuous Running Time	9
Lubrication Quality	SAE10W30 (CD class and above)
Oil Capacity (L)	2
Lubrication Type	Combined force - feed and splash lubrication
Starter	Electric Start
Noise level (dBA) at full load @ 1mt	80
Noise level (dBA) at full load @ 7mt	70

FEATURES / STANDART / OPTIONAL EQUIPMENTS

Fuel Level Gauge	√
Engine Start Key	√
Digital Multimeter	√
AC Circuit Breaker	√
Socket (2x16A)	√
Lamp	√
Wheels & Handler	√
Battery - 22Ah (For electrical start)	√
Counter	√
12V DC Outlet (100W)	√
DC Circuit Breaker	√
Remote Start	O
Automatic Transfer Switch	√
CE Certificate	√
20 Feet	72 Units
40 Feet HQ	90 Units